

10/561186

IAP9 Rec'd PCT/PTO 16 DEC 2005

ENGLISH TRANSLATION OF INTERNATIONAL APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. :

U.S. National Serial No. :

Filed :

PCT International Application No. : PCT/FR2004/001477

VERIFICATION OF A TRANSLATION

I, the below named translator, hereby declare that:

My name and post office address are as stated below;

That I am knowledgeable in the French language in which the below identified international application was filed, and that, to the best of my knowledge and belief, the English translation of the international application No. PCT/FR2004/001477 is a true and complete translation of the above identified international application as filed.

I hereby declare that all the statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the patent application issued thereon.

Date: November 25, 2005



Full name of the translator :

Gwen Jacqueline SANGER

For and on behalf of RWS Group Ltd

Post Office Address :

Europa House, Marsham Way,
Gerrards Cross, Buckinghamshire,
England.

CONTAINER MADE FROM THERMOPLASTIC MATERIAL WITH A DOMED
BASE

5 The present invention relates to improvements made to
containers made of thermoplastic and provided with a
bottom of the type known as a "champagne bottom" (that
is to say a bottom that is steeply domed or dimpled
toward the inside of the container), said bottom
comprising a downwardly projecting central pimple (that
10 is to say one in the concave face of the bottom), a
peripheral bearing region via which the container can
stand stably on a substantially flat support, and ribs
radiating from said central pimple as far as said
peripheral bearing region.

15 So-called "champagne bottoms" offer the advantage of
making it possible to produce a peripheral bearing
region that is flat and above all continuous over the
entirety of its extent, so that they afford the
20 containers placed on a substantially flat support a
remarkably stable footing. Bottoms of this type are
particularly advantageous when the containers are
filled with pressurized liquid (for example fizzy
drinks) because these bottoms, because of their highly
25 inwardly convex shape, are intrinsically able to
withstand the pressure applied to them from the inside,
and therefore remain stable.

However, obtaining these advantageous characteristics
30 entails a sufficient thickness of thermoplastic, which
thickness is appreciably greater than the thickness of
the wall of the body of the containers (see, for
example, document FR 2 730 471) which makes
manufacturing the containers by blow-molding or
35 stretch-blow-molding from heated preforms more tricky.

Numerous embodiment variants of champagne bottoms which
tend toward the obtaining of improved flatness and

stability of said bottoms, often in conjunction with a desire to minimize the thickness of the material and therefore the cost of these containers, are known.

5 It is an object of the invention to propose a novel champagne bottom structure which combines all the advantageous characteristics inherent to this type of bottom while at the same time allowing a saving on the amount of material needed for producing the containers
10 and therefore allowing their cost to be reduced.

To these ends, the invention proposes a container made of a thermoplastic material and provided with a bottom of the "champagne bottom" type comprising a downwardly
15 projecting central pimple, a peripheral bearing region and an intermediate arch provided with ribs radiating from the central pimple as far as the bearing region, which container, being arranged in accordance with the invention, is

20 characterized in that

- the ribs extend from the central pimple as far as the bearing region but exclude this region,
- the ribs are of dihedral shape with a V-shaped cross section the mid-plane of which is substantially
25 parallel to the axis of the container and follow on from one another without discontinuity, and
- the ribs have a longitudinal profile which is curved, the valley bottoms of the ribs, in their region adjacent to the central pimple, coming up higher than
30 the base of said central pimple and the valley bottoms and crests of the ribs, in their regions adjacent to the bearing region, having curvatures which blend gradually into a continuous rounded feature with no break in curvature immediately above
35 the bearing region so that the latter is substantially flat and continuous over its entire extent.

By virtue of this arrangement, the arch of the champagne bottom which extends between the central pimple and the peripheral bearing region has improved mechanical strength not only because of the presence of
5 the ribs but also because of the actual shape of the ribs which, being arranged one after the next without discontinuity, bear against one another and strengthen each other. This mechanical strength is also improved as a result of the special longitudinal profile of each
10 rib, with the valley bottom of each rib which, starting from the central pimple, comes up higher than the latter toward the inside of the container and therefore has a very pronounced curvature with its convex side facing toward the inside of the container, giving it
15 better ability to withstand the pressure.

All these individual characteristics combine with one another to yield a champagne bottom that is stronger than the currently known bottoms and which is therefore
20 capable either, for the same wall thickness as known bottoms, to withstand higher pressures without deformations or, advantageously, of being made with a smaller wall thickness in order to be able to withstand a given pressure.

25 It should be noted here that the possible reduction in thickness relates not only to the arch equipped with said dihedral ribs but also and above all to the peripheral bearing region, the thickness of which is
30 traditionally the greatest.

Advantageously, the central pimple is in the shape of a downwardly projecting circular plateau. This arrangement stabilizes the center of the bottom and
35 gives it a constant geometry, independent of the precise position of the pellet of crystallized material resulting from the process of injection-molding the preform. This, as far as the bottom is concerned,

results in an improved overall shape that is symmetric, making it easier to obtain the flatness of the peripheral bearing region.

5. The arrangements of the invention find application in particular when the container is made of PET.

A favorite application of the arrangements of the invention is when the container is a bottle the overall shape of which is approximately that of a cylinder of revolution and the bearing region is annular and substantially coaxial with the central pimple, the dihedral ribs extending radially. As a preference, this container comprises ribs each having the same angular breadth. In this case, in the typical exemplary embodiment of a bottle with a bearing-region diameter of the order of 45 mm, the bottom of the bottle has ten or so ribs each having the same angular breadth. More generally, it is possible to envisage for the number of ribs to vary substantially with the diameter of the bearing region, particularly between 8 and 16 for standard-diameter bottles.

The arrangements according to the invention may lead to substantial savings in material. By way of example, in the case of a bottle having a capacity of 1.5 liters and a bottom diameter of the order of 70 mm (measured in the bearing region) and provided, as mentioned above, with 10 dihedral ribs, it is possible to obtain a saving of the order of 8 to 15% on material by reducing the thickness of the arch and to make a saving of the same order of magnitude by reducing the thickness in the bearing region, while at the same time obtaining mechanical strength characteristics that are at least identical, or even improved, by comparison with known bottoms.

The invention will be better understood from reading the detailed description which follows of some arrangements according to the invention which are illustrated, by way of example, in the attached drawings in which:

- figure 1 is a diagrammatic view in section of the lower part of a thermoplastic bottle with a bottom formed in accordance with the invention;
- figure 2 is a perspective view from beneath of the lower part of the bottle illustrated in figure 1; and
- figure 3 is a view in section on line III-III of figure 1, of a rib of the bottom in accordance with the invention.

Figures 1 and 2 illustrate, by way of example, the lower part of a bottle 1 the overall shape of which is approximately that of a cylinder of revolution, the side wall 2 of which connects at the lower extremity to a bottom 3 of the "champagne bottom" type, that is to say one steeply domed or dimpled toward the inside.

The bottle 1 is made of thermoplastic, particularly of PET, and manufactured by a process of blow-molding or stretch-blow-molding a preform.

The bottom 3 comprises: a central pimple 4 (consisting of or including the pellet of crystallized material that results from the process of injection-molding the preform), which is advantageously produced in the shape of a downwardly projecting circular plateau; a peripheral bearing region 5, in this instance of annular shape, which extends substantially in a plane so that the container can rest stably on a flat support; and an intermediate region or arch 6 equipped

with ribs 7 radiating from the central pimple 4 as far as the bearing region 5.

5 According to the invention, the ribs 7 extend from the central pimple 4 as far as the bearing region 5 but exclude this region; in other words, the ribs do not encroach upon the bearing region 5 which thus extends continuously in an annulus.

10 In addition, as can be seen in figure 2 and especially in figure 3, the ribs 7 are dihedral in shape, that is to say they are formed of two flat walls 7a, 7b inclined with respect to one another with a V-shaped cross section that is symmetric with respect to the
15 mid-plane 7c substantially parallel to the axis 1a of the bottle and passing through said axis.

As can be seen in figure 2, all the dihedral ribs 7 follow on from one another without any discontinuity so
20 that all the ribs distributed in a circle rest against one another and strengthen each other, leading to an arch 6 that has a better mechanical strength and is better able to withstand the pressure applied to it.

25 As can be seen particularly in figure 1, the ribs 7 have a curved longitudinal profile. The valley bottoms 7d of the ribs, in their region adjacent to the central pimple 4, come up higher than the base of said pimple 4, which means that the valley bottoms 7d in this
30 region have a very pronounced curvature whereas, in the same region, the crests 7e of the ribs diverge from the central pimple substantially at right angles to the axis 1a. This arrangement plays a part in strengthening the arch 6.

35

The valley bottoms 7d and the crests 7e of the ribs 7 have respective longitudinal profiles such that, toward the periphery of the bottom, they have curvatures that

merge progressively into a continuous rounded feature with no break in curvature immediately above (at 8) the bearing region 5, so that this region is flat and continuous over its entire extent.